



- ✓ Flexible control options via voice command, touchpad and control buttons
- ✓ Powerful camera function for video streaming and vision picking
- ✓ Advanced processor for aR applications
- ✓ IEC 60601 certificates for safe use in sensitive areas such as operating theatres
- ✓ Special offer price: € 1.390,- | In stock

## Features

---

Weights only **68 grams** thanks to its minimalist design

---

**Hot-swappable** to prevent downtime when changing batteries

---

**3,350 mAh Anker power bank** included with the Extended Series

---

Large selection of **additional power banks**

---

---

Powerful **runtime of up to 12 hours**, depending on the choice of battery and application

---

Never miss a detail with **autofocus and 4K video streaming at 30 frames per second** through the 12.8 million pixel PDAF camera

---

Protected from water, dust and a **drop of 2 metres, IP67 protection rating**

---

## Optional accessories

---

**Safety glasses frames, small and large available**

---

**Frames without lenses**

---

**Headband**

---

**Hard hat mount**

---

**Peltor headphone mount**

---

---

**Baseball hat**

---

**Baseball hat holder**

---

**various power banks**

---

**Charging cable**

---

**Headband**

---

## OPTICS

- Display resolution: nHD color display
- Display type: OLED
- Aspect ratio: 16:9
- Field of View (diagonal): 16.8 degrees, equivalent to a 5 in. mobile device screen seen at 17 inches
- Brightness: > 2000 nits
- Contrast: > 10,000:1
- 24-bit color with true black
- Supports left or right eye use

## SYSTEM

- 8 Core 2.52Ghz Qualcomm XR1
- 6GB LPDDR4 RAM
- 64GB internal flash memory
- Android 9.0 OS
- OS and apps OTA upgradeable
- MDM available from multiple partners

## CERTIFICATIONS<sup>2</sup>

- Drop safe to 2 meters
- IEC60601-2:2014 Medical Device
- IP67 rated protection against water and dust (Longevity Series)

## UNIVERSAL M-Series RAIL FOR VARIOUS MOUNTING OPTIONS

- Vuzix M-Series Rail Eyeglass frames without lens (standard)
- Weighs less than 3 oz.
- Eyeglass frames with lens
- Safety glasses
- Hard hat mount
- Headband mount
- Peltor headphone mount

## BATTERY

- 135mAh internal battery supports hot swapping of external batteries
- 750 mAh IP67 certified USB-C battery with 3-level LED indicator (Longevity Series)
- Extended life 3350 mAh USB-C battery (Extended Series)
- Can be powered by 3rd-party USB battery packs in place of head-worn battery
- 2 – 12 hours of operation based on external battery choice

## CONTROLS

- 3 control buttons
- Voice control – customizable and supports multiple languages
- 2 axis touchpad with multi-finger support

## AUDIO

- Integrated speaker (up to 97db output)
- Triple noise-cancelling microphones
- BT audio: HSP / A2DP

## CAMERA

- Up to 12.8-megapixel stills
- Up to 4k30 video
- Improved auto-focus (PDAF)
- Improved optical image stabilization
- LED flash/scene illumination
- Barcode scanning

## CONNECTIVITY

- USB 3.1 Gen 2 on USB Type-C
- Wi-Fi 2.4/5Ghz 802.11 a/b/g/n/ac
- Bluetooth 5.0 BR/EDR/LE

## INTEGRATED HEADTRACKER

- 3-degree of freedom head tracking
- 3 axis gyro
- 3 axis accelerometer
- 3 axis mag/integrated compass

## GPS

- GPS / GLONASS

## ENVIRONMENT

- Operating temperature -20°C to 45°C/-4°F to 113°F
- Operating humidity 0-95% RH
- Storage temperature 10-45°C
- Storage humidity 0-95% RH